



Technical data:

Max. operating pressure	350 bar
Max. flow	240 l/min
Max. internal leakage	4 cm³/min (*)
Fluid temperature range	-30/+100 °C
Installation torque	208-234 Nm
Weight	1.00 kg
Cavity	003 (special)
Seal kit	RG0003020520100 (**) R930001695
Fluids	Mineral based or synthetics with lubricating properties at viscosities of 10 to 500 mm²/s (cSt)
Filtration	Nominal value max. 10 µm (NAS 8) ISO 4406 19/17/14

(*) At 80% of pressure setting
(**) Only external seals for ten valves

Z	Springs		
	Adj. press. range bar	Press. increase bar/turn	Standard setting (bar) Q=5 l/min
10	35-100	18	100
20	70-210	36	200
35	120-350	62	350

Denominazione / Denomination		VSD-250		 Bosch Rexroth Oil Control S.p.A. Ufficio Tecnico Technical Dep. DC-MA/ECC1 Gerarchia Prodotto 871117601 Product Hierarchy Kit guarniz. RG0003020520100 Seal kit Modifiche <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr></table> Changes Sostituisce il - Replaces Codice 0415039299Z Code Material number -						
Specifiche / Specifications	-	Cliente e codice articolo / Customer and article code	-							
Richiesta / Request	UT11950	Num. schema idraulico / Hydraulic scheme no.	bs_0010							
Tipo cavità / Cavity type	003	Studio di riferimento / Reference study	-							
Disegnato / Designed by Moretti		Data / Date	20/12/12							
Verificato / Checked by Tagliazucchi		Scala / Scale	1:1							
Direttore del file Cad / Cad file directory K:\Design\Cad 3D\Ingombri\0415039299Zi										