



Max. Operating Pressure : 420 bar
 Max. flow : 350 l/min

PRESSURE SETTINGS
 Valve 1 : 7.5 bar Cracking pressure
 Adj. Pressure range : 6-20 bar
 Pressure increase : 5.7 bar/turn

Valve 2 : 350 bar (Q=5l/min)
 Adj. Pressure range : 350-460 bar
 Pressure increase : 228 bar/turn

Port Size :
 V2-C2 = 3/4 SAE 6000
 E-Pil-T = G 1/4 ISO 1179-1

Manifold : Zinc plated steel
 External parts : Zinc plated steel

Seal flange kit : E0000000000002 (MNR:R930004532)

LABEL/ETICHETTA NP169

For dimensions without tolerance, consider $\pm 0.5\ \text{mm}$

Specifiche	-	Coppia di serraggio	-
Identificazioni	-	Installation torque (Nm)	-
Accessori	-	Kit guarniz.	E00000000000002
Materiali	-	Seal kit	R930004532
Tipo cavità	-	Cliente e codice articolo	-
Cavity type	-	Customer and article code	-
		Codice articolo	084785037218010
		Customer code	-
AA	20230123	TLR1C DB	sar2cob
Ind. Change/Mod.	YYYYMMDD	Drawn/Dis.	gk
Lang./Lin.	EN/IT	Scale/Scala	1:1
EN/IT	12.100	Mat.meets/Mat.ves	N2580-1
Doc. type	AGZ	Syst.	PE
Formal	RB02525491	Repl. by	-

© Bosch Rexroth AG. All rights reserved. Also regarding any disposal, in the event of applications for industrial property rights.