



Max. pressure: 600 bar
Max. flow: 400 l/min

PRESSURE SETTINGS
Valve 1:
8 bar cracking pressure
Adj. pressure range: 3-15 bar
Pressure increase: 3,4 bar/turn

Valve 2:
350 bar cracking pressure
Adj. pressure range: 350-460 bar
Pressure increase: 228 bar/turn

Port size:
V2-C2 = 1 SAE 6000
E-P11-T = G1/4 ISO 1179-1

Manifold: (zinc plated) steel
Seal: BUNA N-70 SHORE

For dimensions without tolerance, consider ±0.5 mm

All dimensions : mm

Denominazione / Denomination A-VBC42R-FC100SAE6000-60C		 Bosch Rexroth Oil Control S.p.A. Ufficio Tecnico Technical Dep. DC-MA/ECM Gerarchia Prodotto Product Hierarchy - Kit guarniz. Seal kit - Modifiche Changes Sostituisce Replaces 08479303736000B Codice Code 08479303736000C Material number R930008391	
Specifiche Specifications	-		
Massa / Mass (kg)	11.547	Cliente e codice articolo Customer and article code	-
Richiesta / Request	UT10934	Num. schema idraulico / Hydraulic scheme no.	-
Tipo cavità Cavity type	A3	Studio di riferimento / Reference study	-
Disegnato / Designed by Giuliano Data / Date 02/12/13		Verificato / Checked by Berselli Scala / Scale 1:2	
Direttorio del file Cad / Cad file directory K:\Design\Cad 3D\Ingombr\08479303736000C			

MODIFICHE
CHANGES