


4/3 and 4/2 Proportional directional valve elements with LS - Electrohydraulic actuation

EDG-PP

RE 18301-24

Edition: 11.2025

Replaces: 06.2025



- ▶ Size 6
- ▶ Maximum operating pressure:
 - 350 bar (5000 psi) on pump side
 - 350 bar (5000 psi) on consumer side
- ▶ Maximum flow at 11 bar (160 psi) bias spring: 60 l/min (15.8 gpm)
- ▶ Ports connections G 3/8 - G 1/2 - SAE8

General specifications

The inlet section can be configured for either a fixed displacement pump or load-sense variable displacement pump. When simultaneous machine functions are actuated, the pre-compensators will automatically adjust to the highest load pressure via a shuttle arrangement, making the system circuit independent of variations in loads and pump pressures. Thanks to modularity concept, it's possible to combine stacks of flexible sections across the entire EDG family; this enables to build up a valve group that meets specific requirements.

Furthermore: compactness, power density and energy efficiency thanks to low Dp complete the best in class performance.

Main Field of Application

Truck mounted applications
Forestry machinery
Forklifts and Telehandler
Municipal vehicles
Cranes
Construction machines
Mobile elevating working platforms
Heavy duty vehicles
Agricultural machines

Contents

Ordering details	2
Ordering details	3
Hydraulic layouts	4
Functional description	5
Technical data	6
Characteristic curves	7
External dimensions and fittings:	
- Standard version	8
- Emergency lever option	9
Electric connections	10

Ordering details

00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19
EDG	-	PP	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Family

00	Directional Valve elements EDG Size 6	EDG
----	---------------------------------------	------------

Type

01	Electro - Piloted proportional	PP
----	--------------------------------	-----------

Component Series

02	Series 1	1
----	----------	----------

Ports & Connections

03	G 1/2 DIN 3852	G12
	3/4-16 UNF 2-B (SAE8)	S08

Local compensator bias spring

04	8 bar (116 psi)	2
	11 bar (160 psi)	4

Flange configuration

05	With P-TA-TB-LS-YA-YB-X-Y lines	2
	With P-TA-TB-LS-YA-YB-X-Y lines and LS return line	3

Hydraulic connections in neutral

06	P, A, B closed and LS to T	B
	P closed and A, B, LS to T	E

Spool variants

07	4/3 operated both sides A and B	2
	4/2 operated side A	3
	4/2 operated side B	4

Flow rates over valve connection (according to table 1)

08	Flow rate P>A	-
09	Flow rate P>B	-
10	Nominal flow rate (A>T)	-¹⁾
11	Nominal flow rate (B>T)	-¹⁾

Voltage supply

		01	03	04	17	
12	12V DC	●	●	●	●	OB
	24V DC	●	●	●	●	OC

● = Available - = Not available

Electric connections ¹⁾

13	With coils, with connection DIN EN 175301-803	01²⁾
	With coils, with connection vertical Amp - Junior	03
	With coils, with connection orizontal Amp - Junior	04
	With coils, with connection vertical DT04-4P	17

Secondary valve types

14	Without secondary valve	00
	Double or single full relief valve with Anticavitation (VMA) or anticavitation only (VUM) or plug	M0³⁾
	Double or single LS relief valve (VMGLS) or plug	0M⁴⁾
	Combination of M0 and 0M options together	MM

Secondary valve config. setting:

Full Relief or Anticavitation selection (according to table 2)

15	A>Ta setting @5lpm	-⁵⁾
16	B>Tb setting @5lpm	-⁵⁾

Secondary valve config. setting: LS Relief (VMGLS) (according to table 3)

17	LSA>T	-⁵⁾
18	LSB>T	-⁵⁾

Override option & Emergency Lever

19	Lever type manual override on A side – Horizontal	HA⁵⁾
	Lever type manual override on A side – Vertical	VA⁵⁾
	Prepared for level type manual override on A side	XA⁶⁾
	Lever type manual override on A side - Horizontal 180° rotated	H1⁵⁾
	Lever type manual override on A side - Vertical 180° rotated	V1⁵⁾
	Prepared for lever type manual override on A side - 180° rotated	X1⁶⁾

1) Only symmetrical spools available.

2) For mating connectors ordering code see data sheet RE 18325-90. Other connectors available on request

3) For fixed setting relief valve data sheet see Data Sheet RE 18329-11. For anticavitation valve data sheet see Data Sheet RE 18329-51.

4) See Table 3.

5) "0" option is the only one available for "Without secondary valves" selection.

6) Selecting option "Prepared for lever type override", the lever K-2316 (R930083885) is included as spare item.

Ordering details

Table 1

	Spring Setting	
	8 bar	11 bar
	3333	28 ¹⁾
	33 ¹⁾	
Spool Variant	6666	38 ¹⁾
	45 ¹⁾	
	9999	52 ¹⁾
	60 ²⁾	

1) With minimum inlet standby pressure of 14 bar (203 psi) - ($P_p - P_{LS}$)

2) With minimum inlet standby pressure of 18 bar (261 psi) - ($P_p - P_{LS}$)

Table 2

Full relief valve configuration setting

0				9				8			
Without valve cavity on both sides (not drilled)				With valve cavity plugged (Normally closed plug)				With anti-cavitation valve			
A	B	C	D	E	F	G	H	I	J	K	
50 bar	60 bar	70 bar	80 bar	90 bar	100 bar	110 bar	120 bar	130 bar	140 bar	150 bar	
725 psi	870 psi	1015 psi	1160 psi	1305 psi	1450 psi	1595 psi	1740 psi	1885 psi	2030 psi	2175 psi	
L	M	N	O	P	Q	R	S	T	U	V	X
160 bar	170 bar	180 bar	190 bar	200 bar	210 bar	220 bar	230 bar	240 bar	250 bar	270 bar	290 bar
2320 psi	2465 psi	2611 psi	2756 psi	2901 psi	3046 psi	3191 psi	3336 psi	3481 psi	3626 psi	3916 psi	4206 psi

Note


For pressure higher than 290 bar (4206 psi), contact factory.

Table 3


LS relief valve configuration setting

Option selection	Description	Standard setting (bar)
0	without valve cavity	-
1	30-90 bar (Setting range)	70
2	80-140 bar (Setting range)	110
3	135-225 bar (Setting range)	180
4	210-310 bar (Setting range)	250
5	290-380 bar (Setting range)	300
9	Normally closed plug	R930082023

Hydraulic layouts




14 - Secondary valve types




00

No secondary valves




0M

LS relief valves option




M0

Relief valves with anticavitation option



M0


Anticavitation valves option




MM

Combination of M0 and 0M options

07 - Spool Variants



Functional description



- 1 Housing
- 2 Main spool
- 3 Return Spring
- 4 Piloting module
- 5 LS shuttle valve
- 6 Compensator spool
- 7 LS relief valve (VMGLS)
- 8 Secondary valve with anticavitation option

The EDG pilot operated proportional sectional valves with pressure compensation control the oil flow to actuators. These elements consist of a stackable housing (1) with a control spool (2), a piloting module (4), one return spring (3). The piloting module (4), energized by PWM regulator, displaces the control spool from its neutral-central position "0" proportionally to the current received. When the spool is shifted and the metering notch is open, flow delivery starts and is controlled by a 2 way pressure compensator (6) ($P > A$; $P > B$).

When the pilot module is de-energized, the return spring pushes the spool back in its neutral-central position.

Load pressure compensation

The pressure compensator (6) keeps the pressure differential on the main spool (2). The flow to the consumers remains constant, despite varying loads. The highest load pressure on the pump is signaled via the LS line and the integrated shuttle valve (5).

Port relief valves with anti-cavitation function on A and B (8) protect the system against pressure peaks and cavitation. LS relief valves (7), for each consumer port, can be adjusted according to specific application requirements.

Technical data





General			
Valve element	kg (lbs)	2.2 (4.85)	
Ambient Temperature	°C (°F)	-30...+60 (-22...+140)	
Body valve zinc plating treatment for higher corrosion resistance protection	h	up to 500	
Hydraulic			
Maximum pressure at P, A and B ports	bar (psi)	350 (5000)	
Maximum static pressure at T	bar (psi)	30 (435)	
Max. regulated flow at 8 bar (116 psi)	l/min (gpm)	60 (15.8)	
For E schemes symmetrical spool pattern in neutral position (connection A to T and B to T).		Approx. 3% of the nominal cross-section	
Hydraulic fluid General properties: it must have physical lubricating and chemical properties suitable for use in hydraulic systems.		Mineral oil based hydraulic fluids HL (DIN 51524 part 1). Mineral oil based hydraulic fluids HLP (DIN 51524 part 2). For use of environmentally acceptable fluids (vegetable or polyglycol base) please consult us.	
Fluid Temperature	°C (°F)	-30....+100 (-22....+212) (NBR seals)	
Permissible degree of fluid contamination		ISO 4572: $\beta_x \geq 75$ X=12...15 ISO 4406: class 20/18/15 NAS 1638: class 9	
Viscosity range	mm²/s	20....380 (optimal 30....46)	
Electrical			
Voltage type	PWM	200 Hz	
Voltage tolerance (nominal voltage)	%	-10 +10	
Insulation class		F	
Compliance with		Low Voltage Directive LVD 73/23/EC (2006/95/EC), 2004/108/EC	
Pilot module weight	kg (lbs)	0.400 (0.881)	
Voltage	V	12	24
Nominal 100% current	A	0.98	0.49
Nominal Coil Resistance at 20°C (68°F)	Ω	6.9	27.8

Note

For applications with different specifications consult us.


* In addition to relief valve pressure setting value.

Characteristic curves




Measured with hydraulic fluid ISO-VG32 at $45^\circ \pm 5^\circ \text{C}$ ($113^\circ \pm 9^\circ \text{F}$); ambient temperature 20°C (68°F).

External dimensions and fittings - Standard version



- 1 Identification label.
- 2 Flange specifications. For tie rod and tightening torque information see data sheet RE 18301-92.

External dimensions and fittings - Emergency Lever option

Electric connections

01 Protection class: IP 65 when connector with seal is properly screwed down. 1)	03 Protection class: IP 67 whit female connector properly fitted (see drawing). 2)
17 Protection class: IP 69K whit female connector properly fitted (see drawing). 3)	04 Protection class: IP 67 whit female connector properly fitted (see drawing). 4)

Bosch Rexroth Oil Control S.p.A.

Oleodinamica LC Division
Via Artigianale Sedrio, 12
42030 Vezzano sul Crostolo
Reggio Emilia - Italy
Tel. +39 0522 601 801
Fax +39 0522 606 226 / 601 802
compact-hydraulics-cdv@boschrexroth.com
www.boschrexroth.com/compacthydraulics

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth Oil Control S.p.A.. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging. Subject to change.