



Dimensions in mm

Technical data	
Max. pressure	250 bar
Max. flow	90 lpm
Weight	2,2 Kg
Manifold material	Aluminum
M port	1/8" G
M-LS port	1/4" G
P / T ports	1/2" G

N°	Description	Q.ty
1	M8x15 thread for mounting	2
2	Pressure compensator	1
3	Bosch Rexroth coil D36 - CLASS H DIN 43650 ISO 4400 *	1
4	Bosch Rexroth solenoid valve OD.15.06.21-Y-00000	1
5	Connector DIN 43650 ISO 4400	1
6	M8x15 for tie rod	3

* for complete technical information, click on the blue link or go to the components section at the end of the catalogue

Ordering code

H	3	2	1	3	A	-	-	-	-	-	-	-
---	---	---	---	---	---	---	---	---	---	---	---	---

Hydrover product

Product series

32 series - Load sensing modular Cetop 3 subplates for parallel circuits

Product ID

Manifold material

Aluminum

Compensator spring

5.5 bar (standard) = 6
 12.5 bar = 1
 19 bar = 2

Solenoid valve coil connection *

1 = DIN 43650 ISO 4400

Solenoid valve coil voltage *

OB = 12V DC
 OC = 24V DC
 OD = 48V DC
 OU = 110V RAC
 AH = 230V RAC

Solenoid valve manual override *

E0 = Without
 EP = Push (NA, 2A)
 EG = Push and twist (NA, 2A)

