



Dimensions in mm

N°	Description	Q.ty
1	Bosch Rexroth proportional solenoid valve VEP-5B-2S-D / <a href="#">OD.94.01.18-Y-Z</a> * as depicted with screw manual override	1
2	Bosch Rexroth coil <a href="#">S5-356</a> - CLASS H DIN 43650 ISO 4400 *	1
3	Connector DIN 43650 ISO 4400	1
4	Ø 5,5 through hole for mounting	4
5	OR 108 i. Ø 8,73 cross section 1,78	2

\* for complete technical information, click on the blue link or go to the components section at the end of the catalogue

Ordering code

H	3	5	0	2	S	-	-	-	-	-	-	-
---	---	---	---	---	---	---	---	---	---	---	---	---

**Hydrover product**

**Product series**

35 series - Cetop 3 valves

**Product ID**

**Manifold material**

Steel

**Proportional solenoid valve manual override \***

Without

= E0

Screw (standard)

= EV

**Proportional solenoid valve coil connection \***

1 = DIN 43650 ISO 4400

**Proportional solenoid valve coil voltage \***

OB = 12V DC

OC = 24V DC

**Proportional solenoid valve pressure adjustment range \***

1 = 15-140 bar

2 = 30-250 bar

3 = 30-350 bar

\* Omit if not required. For example, to order the product without the proportional solenoid cartridge valve, omit the manual override, pressure range, coil voltage and coil connection options: H3502S.  
The manifold will still be provided with the corresponding cavity.