



Ordering code

H 4 2 0 7 A - - -

**Hydrover product**

**Product series**

42 series - Load sensing plates for Bosch Rexroth ED bankable valves

**Product ID**

**Manifold material**

Aluminium

**Pressure reducing valve type \***

R = VRPR-10A (direct)  
X = VRPX-10A (pilot)

**VRPR-10A reducing valve pressure range (static) \***

0 = 2-14 bar  
1 = 2-25 bar  
2 = 10-50 bar  
3 = 28-80 bar

**VRPX-10A reducing valve pressure range (static) \***

0 = 25-100 bar  
1 = 35-140 bar  
2 = 70-280 bar  
3 = 35-350 bar (adj. knob)

**Reducing valve adjustment type \***

S = Screw  
K = Knob

\* Omit if not required. To order the product without the reducing cartridge valve, omit the adjustment type, pressure range and valve type options: H4207A.  
The manifold will still be provided with the corresponding cavity.

N°	Description	Q.ty
1	Ø 7,5 hole with OR 2043 i. Ø 10,82 cross section 1,78 (P-T)	2
2	LS through hole with counterbore on one side for OR 2021 i. Ø 5,28 cross section 1,78	1
3	Ø 8,5 through hole for tie rod	3
4	Bosch Rexroth reducing valve <b>VRPR-10A</b> o <b>VRPX-10A</b> * depicted with screw adjustment	1

\* for complete technical information, click on the blue link or go to the components section at the end of the catalogue

Technical data	
Max. pressure	250 bar
Max. flow with VRPR-10A	25 lpm *
Max. flow with VRPX-10A	55 lpm *
Weight	0,7 Kg
Manifold material	Aluminium

Can be used with LS or non LS elements.

